



mV Plus for a wide range of applications

Technical Information

Shade availability

mV Plus is available in a comprehensive range of shades. For more information on availability please contact the Customer Service Team at your local API Foils office.

Operating Temperatures

- Platen: 80 to 130°C
- Cylinder: 110 to 150°C
- Rotary: 140 to 210°C

Resistance Properties

- Good resistance to abrasion in graphics applications (STM05)
- Excellent resistance to Water (STM06)
- Excellent resistance to Wines & Spirits (STM07)
- Excellent resistance to Plasticiser migration (STM08).

Light-fastness -

In order to maintain a consistent brand image and aesthetic appeal it is important that foil used on products and packaging does not significantly fade when subjected to a high degree of daylight. In response to this API has undertaken research into the light-fastness of foils.

If you would like further information on this subject please contact the Market Support Team at API Foils.

As foils are heat-activated, do not store or transport foil reels at high temperature or humidity.

As with all foils, we would advise that ideal storage conditions should avoid condensation and undue pressure. We would recommend that foil be stored at between 5 and 20C (and out of direct sunlight) and 30 – 70% relative humidity.

Toxicity

Mv Plus is classed as “Non-toxic” and meets stringent legislation of numerous National and International industry standards, including –

- CONEG
- EN71.3 and EN71.9, 10, 11
- BS5665 PART 111 1995
- ASTM F963-96a US CPSC
- RoHS-2002/95/EC
- The European Packaging (Essential Requirements) Regulations 1998 SI: 1165, 1998

www.apifoils.com

UK: +44 (0) 1506 438611. France: +33 (0) 1 69 75 43 21. Germany: +49 (0) 912 263 040. Italy: +39(0) 131 23 36 17

Other European markets: +44 (0) 1506 438611. Hong Kong: +852 3426 4908

API Foils Ltd. Issue date Sept 2007